



Shandong Zhuoxing Chemical Co., Ltd.

Zibo Zhuoxing Enterprises Co., Ltd.

TDS of SPS-06 Water Reducing Type Polycarboxylate Superplasticizer PCE Powder

Description

SPS-06 is a new generation of Eco-friendly high performance polycarboxylate ether superplasticizer powder developed by our company with DD-909 (TPEG2400) as main raw material.

Technical Principle

The main chains of the high performance polycarboxylate water reducing agent molecular are absorbed onto the surface of the cement granules, which can effectively hinder the hydration, enhance fluidity retention ability, the branch chains surrounded by the cement granules, play dual roles of steric hindrance and electrostatic repulsion, it is totally different from conventional water reducing agents, so the high performance polycarboxylate water reducing agent has better dispersion and water reducing effect.

Advantages/Characteristics:

- 1) Polycarboxylate ether superplasticizer powder with solid content : 97% min. (**If it is used for ready mix concrete or precast concrete, please add PCE powder to water to get a solution with solid content 20% or 10% before use**).
- (2) With a high slump retention ability, enhance cohesion, without concrete segregation.

Web site:www.zhuoxingchem.com



Shandong Zhuoxing Chemical Co., Ltd.

Zibo Zhuoxing Enterprises Co., Ltd.

(3) With a good dispersion, an excellent adaptability to different cements, and good water-reducing properties.

Usages and Cautions:

(1) A recommended dosage is 0.16%-0.4% by the weight of cementitious materials. Actual dosages should be determined by mixture design test according to concrete strength grade.

(2) Concrete test must be carried out before utilization.

(3) This product is forbidden to be mixed with naphthalene sulphonate.

(4) Compatibility test must be done when it is used together with other admixtures.

Package: Packed in 25kg plastic woven bags with PE inner liner, 16 mt with pallets loaded in one 20'GP, 27 mt with pallets loaded in 40'HQ by sea, 25.5 mt with pallets loaded in 40'HQ by train

Shelf time: 0°C-40°C the shelf life is 12 months.

Application

1. It is applicable to various ready mix concrete, precast concrete and **especially dry mix mortar**. It can also be used for **oil well cementing operation**.

2. It is particularly applicable to various construction works with high performance requirements for the concrete, such as water industry, marine works, seaports, traffics, electric powers etc.

Web site:www.zhuoxingchem.com



Shandong Zhuoxing Chemical Co., Ltd.

Zibo Zhuoxing Enterprises Co., Ltd.

3. It is applicable to the special concrete, such as high strength, high durability, self-compacting concrete.

Quality Specification

Item	Unit	Standard
Appearance	/	White or light yellow powder
Density	kg/m ³	500±50
pH (23°C)	/	6.0±1.0
Solid Content	%	97.0±1.0
Moisture content	%	≤3.0
Water Reducing Ratio	%	≥25
Cl ⁻	%	≤0.02
Alkali content	%	≤0.3

Contact information:

Shelly Cui

Ella Yang

The seller: Zibo Zhuoxing Enterprises Co., Ltd.

Web site:www.zhuoxingchem.com



Shandong Zhuoxing Chemical Co., Ltd.

Zibo Zhuoxing Enterprises Co., Ltd.

Add: Room 1103, 11th Floor, Yunlong Plaza B, No.28 Huaguang Road,
Zhangdian District, Zibo City , Shandong Province, China 255000

Manufacturer: Shandong Zhuoxing Chemical Co., Ltd.

Add: Xinhai Industrial Zone, Wudi County, Binzhou City, Shandong
Province, China

Tel/Fax:0086 533 2284032

Mobile/ Wechat:0086 13053363281, 0086 18615126163,
0086 17865273019

Mail:sales@zhuoxingchem.com shellypce@hotmail.com

sales02@zhuoxingchem.com

Web site:www.zhuoxingchem.com

<http://sdzhuoxing.en.alibaba.com>

<https://www.sdzhuoxingpce.com>

Web site:www.zhuoxingchem.com